

"Prestige" thermostatic heads

GS.02, GS.03, GS.04

Thermostatic heads meet the requirements of PNEN 215: 2005 PNEN 215; 2005 / A1: 2006

Range	8°C - 30°C* (16°C - 30°C)
Maximum external temperature	50°C
Closure time	16 min
Pressure difference impact	<1K
Hysteresis	0,3K
Heating factor temperature impact	1,23K

*=At the customer's request, the temperature control range can be limited in the factory according to the values

given in the setting scale. The customer can also do this on their own. To do this, use the small flat screwdriver

to remove the spare when setting "6" locking pin embedded in the hole with the number "0" and insert it into

another hole, eg with the number "6" for a maximum temperature of 24 ° C, etc., as desired. To limit the

minimum temperature in the room to 16 ° C, place the locking pin in hole No. 2 and set the viewfinder to "2".

Application:

The "Prestige" thermostatic head is a radiator temperature controller with a modern, ergonomic shape. It allows you to maintain the desired thermal comfort in the room while taking into account gains heat from other sources, e.g. heat gain from people, lighting, and sunlight.

Due to its design, it guarantees easy cleaning, which is why

irreplaceable in hospital, sanatorium, school rooms etc. The GS02 thermostatic head

is adapted to work with radiator valves: • Vario Term type SFP and SFK •

Heimeier • Honeywell V100 and V2000 series • Schlösser style TecSets.

Features:

- Reliable liquid sensor
- Control knob with digital marking Frost
- protection function for the installation (8 ° C at setting "**")
- Body made of high-quality plastic

Assignment of setpoint values to characters on the control knob

•	1	2	3	4	5	6
8°C	12°	16°	20°	24°C	28°	30°C

The management system operating at Vario Term for the production of thermostatic heads compliant is with ISO 9001: 2008 and confirmed with SGS certificate. We offer 3 years warranty for thermostatic heads.

Dimensions

